

AsRex DS - Wellenschutzkappen

- Zylindrische Antriebswellen und Passfeder Sicherung
- Material: LD-PE
- Standard Farbe: Gelb
- Für Wellenenden nach:
 - ⇒ DIN 748
 - ⇒ DIN 42673-1
 - ⇒ IEC 600-72
 - ⇒ ISO R775

Artikelnr.	Durchmesser W	Flansch D	Länge L	Packung
DS9	9.0	14.5	24.0	4.000
DS11	11.0	17.5	27.5	4.000
DS14	14.0	22.5	35.0	4.000
DS15	15.0	25.5	32.0	4.000
DS16	16.0	25.5	47.0	1.100
DS19	19.0	30.5	47.0	1.150
DS20	20.0	32.0	58.5	1.150
DS22	22.0	35.0	58.5	650
DS24	24.0	38.5	58.5	500
DS25	25.0	40.0	70.0	450
DS28	28.0	45.0	70.0	375
DS30	30.0	48.0	93.5	225
DS32	32.0	51.0	93.5	250
DS35	35.0	56.0	93.5	200
DS38	38.0	61.0	93.5	200
DS42	42.0	66.5	126.0	90
DS45	45.0	72.0	117.5	90
DS48	48.0	77.0	127.5	90
DS55	55.0	88.0	127.5	90
DS60	60.0	96.0	164.0	90
DS65	65.0	102.5	163.0	25
DS75	75.0	112.0	164.0	20

